



INTERNAL RATCHETING OUTPUT GEAR

RATED VOLTAGE: 120 VAC, 60 Hz  
 ROTATION: CW  
 NO LOAD SPEED: 2.2 RPM  
 NO LOAD CURRENT: 0.11 A

LOADED SPEED @ 20 IN-LB: 2.0 RPM  
 LOADED CURRENT @ 20 IN-LB: 0.12 A  
 STALL TORQUE: 70 IN-LB  
 STALL CURRENT: 0.16 A

I/WE CERTIFY THAT SAMPLES OF THIS MOTOR HAVE BEEN FULLY TESTED BY THE UNDERSIGNED AND THAT ALL SPECIFICATIONS HAVE BEEN REVIEWED FOR PRODUCTION. MULTIPRODUCTS COMPANY, INC. IS NOT RESPONSIBLE FOR MOTORS THAT FAIL IN THE FILED DUE TO INSUFFICIENT TESTING OF THE SAMPLE MOTORS. I/WE AGREE TO PROVIDE MULTIPRODUCTS COMPANY, INC. WITH CURRENT DRAWINGS AND IN-HOUSE TEST PROCEDURES AS THEY BECOME AVAILABLE. ANY CHANGES THAT I/WE MAY MAKE WHICH OCCUR AFTER THE DATE SHOWN ARE SUBJECT TO REVIEW AND MAY AFFECT UNIT PRICE AND/OR DELIVERY DATES.

A	REDRAWN	4/21/2014	
REV.	DESCRIPTION	DATE	ECO#

**TOLERANCES**

X.XX:  $\pm$  .010  
 X.XXX:  $\pm$  .005  
 FRACTION:  $\pm$  1/64  
 ANGLE:  $\pm$  2°  
 UNLESS OTHERWISE SPECIFIED



**MULTI PRODUCTS**  
 Company, Inc.

PART NAME/DESCRIPTION: <b>AM WARMING</b>			
DRAWN BY: PJ	DATE: 6/8/2009	SCALE: 0.5:1	MATERIAL: SEE BOM
CHK'D BY: -	DATE:	PART NUMBER: <b>MOD-UL14V-3159A</b>	
APPR'D BY: -	DATE:		

SIGNATURE \_\_\_\_\_ PRINT NAME \_\_\_\_\_ DATE \_\_\_\_\_  
 IN ORDER TO BEGIN PRODUCTION, MULTIPRODUCTS COMPANY, INC. MUST HAVE SIGNED APPROVAL.