



# **Gearbox Specifications**

The 400 Series "Open Frame" shaped gearbox is a low-profile gearbox for tightly spaced applications. Able to handle a continuous torque rating up to 50 in-lb with output shaft diameters ranging from 1/4" through 5/16". Best for light duty applications such as hot dog rollers and food stirrers. Other options: multiple gearing materials, needle or ball bearings, and custom wiring harnesses.









Applications: Foodservice Equipment, Gaming, Industrial Machinery, and HVAC Equipment

#### Features:

- Zinc die-cast housing
- Industry mounting options on both sides of gearbox
- Permanently lubricated with synthetic gear grease
- Clutch option
- Noise-reducing phenolic high-speed gearing

## **400 AC GEARMOTOR**

## Information and Specifications



# Compatible AC Motor Options



AC Motor	Shaded Pole	
Voltage	24 - 480 V	
Frequency	50 / 60 Hz	
Rated Speed	3000 RPM	
Rated Torque	Up to 11 in-oz	
Rotation	Uni-directional	

### **AC Gearmotor Performance Specifications**

Core Stack Size	Voltage	Rated Torque	Rated Speed	Rotation	Shaft Size
0.425"	24 - 240 VAC	0.5 - 45 in-lbs.	2 - 400 RPM	Uni-directional	1/4" to 5/16"
0.685"	24 - 240 VAC	0.7 - 50 in-lbs.	2 - 400 RPM	Uni-directional	1/4" to 5/16"

