

**FEATURES:**

- INDUSTRY STANDARD MOUNTING PATTERN
- OUTPUT SPEEDS FROM 1-40 RPM
- OUTPUT TORQUE UP TO 200 IN-LB
- AC VOLTAGES FROM 120 THRU 240
- DIE CAST ZINC CASE
- OP SHAFT  $\phi$ .38 TO  $\phi$ .50
- CUSTOMER SPEC'D FLATS, KEYWAYS, HOLES, ETC

<b>STACK SIZE "X"</b>	.63	.75	1.06	2.00
<b>OVERALL SIZE "Y"</b>	3.03	3.16	3.48	4.41

**TOLERANCES**


X.XX :  $\pm$ .010

X.XXX :  $\pm$ .005

FRACTION:  $\pm$ 1/64

ANGLE:  $\pm$ 2°

UNLESS OTHERWISE SPECIFIED



**MULTI PRODUCTS**  
Company, Inc.

PART NAME/DESCRIPTION: **9000-AC, 6 FRONT, 0 REAR PADS**

DRAWN BY: DAB      DATE: 10/11/2017      SCALE: 0.75:1      MATERIAL: -

CHK'D BY:      DATE:      PART NUMBER: **MOD-9000-AC**

APPR'D BY:      DATE: